

# AR EVOLUTION SERIES

## DOUBLE WALL INSULATED MIXING ROOMS



**Col-Met AR Paint Mixing Rooms** are our double-wall insulated models that provide a clean, contaminant-free environment for paint preparation and mixing. Delivering optimal air circulation and filtration, our mixing rooms effectively remove air particulates that can negatively permeate paints while being processed.

AR Paint Mixing Rooms come standard with exhaust chamber, an air intake plenum, a control panel, personnel door with window and a durable white finish. All models and configurations are UL/ETL Listed.



### Standard Features:

- Double-wall insulated panels
- 12" diameter tubeaxial exhaust fan with 3/4 HP motor
- Exhaust and air intake plenum chambers
- UL/ETL Listed control panel
- Premium durable white finish
- Brixon™ latches on door opening
- Personnel door with observation window 14" x 48"
- Complete exhaust duct package for 17' roof height
- Inside access, four-tube light fixture Class 1, Division 2, ETL Listed

### Options:

- Single skin models
- 3-sided configurations



# AR EVOLUTION SERIES

## DOUBLE WALL INSULATED MIXING ROOMS



Smooth and consistent in performance, air is drawn in through the filtered air intake plenum through the work area and into the exhaust chamber located in the lower opposite end of the room. The filtered exhaust air is then drawn through the exhaust plenum, making a clean discharge into the outside atmosphere through the exhaust stack and providing optimal ventilation.

AR Paint Mixing Rooms are equipped with four-tube, 48", 32-watt, Class 1-Div. 2, fluorescent ceiling panel light fixtures that deliver full booth illumination and enhanced clarity. Each light is sealed behind clear, tempered safety glass, and all fixtures are UL/ETL Listed and approved for their intended use and placement.

**You can achieve particulate-free paint mixes with Col-Met AR Paint Mixing Rooms.**

COL-MET SPRAY BOOTH PRODUCTS COMPLY WITH ALL APPLICABLE OSHA AND NFPA REGULATIONS.



### Standard Specifications

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Lights S&G	Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length				Dia.	HP	Int.	Exh.
AR-PMR-8 7.5	8'-0"	8'-8"	7'-6"	8'-4"	9'-4"	10'-0"	1 with window	1	1930	12"	3/4 HP	4	2
AR-PMR-8 10.5	8'-0"	8'-8"	10'-6"	8'-4"	9'-4"	13'-0"	1 with window	2	1930	12"	3/4 HP	4	2
AR-PMR-8 13	8'-0"	8'-8"	13'-0"	8'-4"	9'-4"	15'-6"	1 with window	2	1930	12"	3/4 HP	4	2
AR-PMR-8 15.5	8'-0"	8'-8"	15'-6"	8'-4"	9'-4"	18'-0"	1 with window	3	1930	12"	3/4 HP	4	2
AR-PMR-8 18.5	8'-0"	8'-8"	18'-6"	8'-4"	9'-4"	21'-0"	1 with window	3	1930	12"	3/4 HP	4	2

#### COL-MET SPRAY BOOTHS

Dallas, Texas  
 Toll-free: 888.452.6684  
 Fax: 972.772.1833  
 evolution@colmetsb.com  
 www.colmetsb.com

